DRIVEN BY AIR.



UK Standard Push Button Safety Coupling

Designed by the only UK manufacturer of Safety Couplings.



Nearly 80 years since PCL first invented of the original UK standard coupling, PCL is pleased to reveal the latest generation of UK Safety couplings.

PCL's new UK Standard Push Button Safety Couplings provide a two-stage, self venting release, eliminating the dangers of hose whip to create a safe compressed air environment.

Built by hand and 100% individually tested for guaranteed reliability in our Sheffield factory, this lightweight but robust coupling comes with a 5 year warranty.

Specifications

Nominal bore: 4.8 mm Max flow rate: 43 cfm @ 100 psi supply Min working pressure: 3 bar / 43.5 psi Max working pressure: 10 bar / 145 psi Temperature range: -20°C to 70°C Interchangeability: Prevost BSI 06, Rectus 19 Material: Seal - Neoprene Spring - Steel Outer body - Glass filled nylon Inners/connectors - Plated steel Type: Two stage push button

A HORNGROUP BRAND

DRIVEN BY AIR.



UK Style Push Button Safety Couplings



Push Button UK Standard Safety Couplings

Part No.	Thread Type	Thread Size
PBS21CM	Male	R 1/4
PBS21EM	Male	R 3/8
PBS21JM	Male	R 1/2
PBS21CF	Female	Rp 1/4
PBS21EF	Female	Rp 3/8
PBS21JF	Female	Rp 1/2
PBS2106	Hose Tailpiece	6 mm
PBS2108	Hose Tailpiece	8 mm
PBS2110	Hose Tailpiece	10 mm
PBS2113	Hose Tailpiece	13 mm

For use with UK Standard Adaptors

Part No.	Thread Type	Thread Size
ACA2593	Male	R 1/4
ACA6909	Male	R 3/8
ACA6584	Male	R 1/2
ACA2746	Female	Rp 1/4
ACA6582	Female	Rp 3/8
ACA6583	Female	Rp 1/2
ACA2486	Hose Tailpiece	4.75 mm / 3/16 in
ACA1793	Hose Tailpiece	6.35 mm / 1/4 in
ACA2487	Hose Tailpiece	7.9 mm / 5/16 in
ACA2488	Hose Tailpiece	9.5 mm / 3/8 in
ACA9438	Hose Tailpiece	13 mm / 1/2 in



P a

PCLDAT084 V1

PCL is the world leader in the design and manufacture of tyre inflation and compressed air products.

Pneumatic Components Limited Holbrook Rise Holbrook Industrial Estate Sheffield S20 3GE